

4

3

2

1

THIS DRAWING UNPUBLISHED.

RELEASED FOR PUBUCATION

LOC

DIST

REVISIONS

P

LTR

DATE

DWN

APVD

D

D

C

C

B

B

A

A

26.4 [1.039]

SMA
MALESMA
MALE

NOTES:

1.ELECTRICAL:



- 1.1 IMPEDANCE: 50Ω
- 1.2 INSULATION RESISTANCE:5000M Ω
- 1.3 FREQUENCY RANGE: DC-18 GHz
- 1.4 DIELECTRIC WITHSTANDING VOLTAGE:
1000V MAX AT SEA LEVEL
- 1.5 VSWR:≤1.2:1 (MAX)
- 1.6 INSERTION LOSS: 0.2 dB (MAX)

2.ENVIRONMENTAL:

- 2.1 TEMPERATURE RANGE: -55° to +165°

3.MATERIAL AND FINISH:

- 3.1 INNER CONDUCTOR MATERIAL:
BERYLLIUM BRONZE GOLD PLATING
- 3.2 EXTERNAL CONDUCTOR MATERIAL:
STAINLESS STEEL PASSIVATION
- 3.3 LNSULATOR: PEI

THIS DRAWING IS A CONTROLLED DOCUMENT		21/10/2021	 Shenzhen xinqiyuan Technology Co., Ltd.					
		CHK						
DIMENSIONSMM		TOLERANCES UNLESS OTHERWIE SPECIFIED: 0 PLC ±0.25 1 PLC ±0.15 2 PLC ±0.12 ANGLES ±1°	APVD					
			APPLICATION SPEC		NAME			
			---		SMA Male TO SMA Male RF Coaxial Adapter			
MATERIAL SEE TABLE		FINISH SEE TABLE	WEIGHT	SIZE A4	CAGE CODE 01021	DRAWING NO SMA/SMA-JJD		
			CUSTOMER DRAWNG		SCALE 2:1	SHEET 1	OF 1	RVE 1

4

3

2

1